

**DMS™ 4.4: Distributed Music System**



**Continuous Power:** 24 watts/channel  
**Peak Power:** 60 watts/channel  
**Frequency Response:** 20 Hz to 20 KHz  
**Power Source:** 12V DC  
**Dynamic Range:** > 100 db  
**Signal-to-Noise Ratio:** > 100 db  
**Maximum distance:** 1000'

The DMS™ 4.4 is a complete multi-source, multi-zone music distribution system with control on a single category 5 wire. It is ideal for restaurants, offices, schools, sports bars, places of worship, manufacturing, production area, and numerous other applications. Its maximum distance on category 5 wires is 1000 ft. from the hub. The DMS™ 4.4 allows you to select from one of four different audio sources in each zone. It features a high performance built-in TV / CATV and FM tuner as the main source. Three additional external sources can be connected to the main distribution hub. Each zone is connected to the main hub by a single category 5 wire.

The in-wall amplifiers with keypads are locally powered (can be centrally powered on an 18 / 2 AWG along with the category 5) and are home run to the main unit. The DMS™ 4.4 has built-in IR remote control distribution. Serial port control of the system allows easy integration with lighting control systems, building automation system, and many others. A PC can also be configured to control the system.

The DMS™ 4.4 system delivers high quality audio at an affordable price. It is a simple yet elegant system that provides unequalled sound quality with cables running up to 250 feet per zone. It distributes audio signals to four listening areas using only a single category 5 wire. Further, each zone is capable of independently selecting any source. The system also features a source selection function, using an IR remote control or a keypad. By cascading additional DMS™ 4.4, the system can be expanded in increments of four zones per unit. Each category 5 wire run ends into an IWA (In Wall Amplifier), for amplification and control.

**Applications:**

**Features & Benefits:**

Multiple room audio system in residential markets  
 Commercial installations in hotels, restaurants, sports bars, shopping malls, arcades, theme parks, gyms, etc.  
 Audio and Video supplied to rooms on category 5 wires  
 In-wall amplification to rooms  
 Cable runs up to 1000 ft.

Easily integrated with TPA™ receiver and the MBA™ amplifier  
 High quality audio  
 Affordable price  
 Easy to operate  
 Simple installation  
 Works off inexpensive wires  
 Eliminates the need for rewiring  
 Cable runs up to 250 ft per zone

Expandable in 4-zone increments  
 Built-in TV/CATV/FM Stereo Tuner  
 Source selection function using an IR Remote Control or keypad  
 4 sources  
 4 zones

Copyright © 1994- 2014. All rights reserved.

**Pragmatic Communications Systems, Inc.**

2340A Walsh Avenue, Santa Clara, CA 95051, USA

Tel. (408) 748 1100

Fax. (408) 663 9783

www.pragmatic1.com

## Architect Specifications:

The unit shall be housed in a standard rack unit. It shall have maximum distance on category 5 wire up to 1000 ft. from the hub. Its cable shall run up to 250 feet per zone. It shall be expandable in 4-zone increments. It shall have each zone capable of independently selecting any source. It shall have a built-in TV/CATV/FM Stereo Tuner. It shall also feature a source selection function, using an IR Remote Control or a keypad. It shall run off category 5 wires with each cable ending into an IWA (In Wall Amplifier), for amplification and control.

The unit shall be a Pragmatic DMS™ 4.4.

Copyright © 1994- 2014. All rights reserved.

***Pragmatic Communications Systems, Inc.***

2340A Walsh Avenue, Santa Clara, CA 95051, USA

Fax. (408) 663 9783

Tel. (408) 748 1100

[www.pragmatic1.com](http://www.pragmatic1.com)