

» IWC™

HideAway™ Series In-Wall Security Camera System

HideAway™ Series In-Wall Security Camera System

The HideAway™ series IWC™ In-Wall Camera System is the ideal choice for an affordable solution to doorway and access point security over category5 twisted pair wires. The high performance 1/3" CCD camera along with associated drive electronics is installed in a single junction box with a RJ45 connector.

The video signal from the camera travels down category 3 or 5 wires to the receiver unit, which can be plugged in to a video monitor and a time-lapse VCR. The power for the camera is conveniently provided on the same category 5 wire so that local power for the camera is not needed at the remote end.

There are a number of optional features available for the IWC™ In-Wall Camera System. Options include a pin-hole lens for covert applications, fish eye lens for wide-angle, C/CS mount adaptor for variety of standard lenses, a starlight / night vision camera (0.05 lux), high resolution color camera, weather-proof single gang enclosure and a tamper-resistant steel face plate.

The unit shall measure 2.4"W x 1.6" H x 1" D and weigh 12 oz. It shall fit in a single gang. Its sensor type shall be 1/3" B/W CCD and have a sensitivity of 0.1 lux. Its resolution shall be 510 x 492 pixels. It shall have auto electronic iris / electronic shutter automated level control. It shall reach distances of 400 ft. It shall be powered by 12 V DC. It shall have the options of pin-hole lens for covert applications, fish eye lens for wide-angle, C/CS mount adaptor for variety of standard lenses, a starlight / night vision camera (0.05 lux), a high resolution color camera, a weather-proof single gang enclosure, and a tamper-resistant steel face plate



Feature & Benefits:

Multiple options including:

- Pinhole lens
- Fish eye lens
- C/CS mount adaptor
- Starlight / night vision camera
- High-resolution color camera
- Weatherproof single gang enclosure
- Tamper-resistant steel faceplate

Specifications:

Sensor Type: 1/3" B/W CCD
 Sensitivity: 0.1 lux
 Resolution: 510 x 492 pixels
 Auto Electronic Iris / Electronic Shutter
 Automated Level Control
 Distance: 400 ft.
 Power: 12 VDC
 Dimensions: 2.4"W x 1.6"H x 1"D
 Weight: 12 oz.

Applications:

- Covert security camera
- Confined space 24 hr security
- Outdoor and indoor applications

*US and International patents pending

TO PLACE an ORDER or for QUESTIONS,
Emails Us: sales@pragmatic1.com, Call Us: (408) 748-1100 or Fax Us: (408) 663-9783