

» PPoE-12

PADS™ Power-over-Ethernet 12VDC

- PADS™ Pragmatic proprietary technology for Power-over-Ethernet receiver with 12VDC output
- Compatible with up to 30W IEEE 802.3at, and backwards compatible with 15.4W IEEE 802.3af standard
- 328 ft./100m transmission distance on standard cat5e/cat6 cables
- Plug-and-play simplicity, simple point-to-point connection with regulated DC output and 10/100/1000 Ethernet output connection
- Energy efficient and very low power consumption
- Circuit isolation protection, effective protection of electrical equipment



Applications:

Background music system
Multi-room audio system
School and college campus
Hospitals/Healthcare facilities
Theme parks/Outdoor events
Health/Fitness clubs
Tanning salons
Hotel Lobbies /Restaurants

TO PLACE an ORDER or for QUESTIONS,
Emails Us: sales@pragmatic1.com, Call Us: (408) 748-1100 or Fax Us: (408) 663-9783

Front View




Rear View



PoE INPUT CONNECTOR	RJ-45
DATA OUTPUT CONNECTOR	RJ-45
POWER OUTPUT CONNECTOR	2.5mm / 5.5mm center positive
POWER OUTPUT	DC 12V @ 2A typical
OPERATING CONDITIONS	Temperature 50°-104°F (10°-40°C), Humidity 20-85% (non-condensing)
WARRANTY	One year limited warranty on parts and labor


Typical application



PX-15

RELATED PRODUCTS

- MuSe™ Music Server
- PA-15R PADS™ in-wall amp with rotary volume control
- PA-15KP PADS™ in-wall amp with IR remote/keypad
- PX-16 PADS™ Amp module
- PTS-1 PADS™ Amplified Tube speaker
- PR-VC PADS™ Rotary Volume Control
- PR-VC PADS™ Keypad Digital Volume Control
- PH4 PADS™ 4-port hub
- PHUSB-3 PADS™ 3-port USB Audio Hub
- PHA Line Array Speakers



TO PLACE an ORDER or for QUESTIONS,

Emails Us: sales@pragmatic1.com, Call Us: (408) 748-1100 or Fax Us: (408) 663-9783