

**Pragmatic PDS42 Digital Signage Monitor** 

Pragmatic Digital Signage Monitor

Model PDS42

## Digital Signage / Retail Advertising Monitor

Brilliant Display and Ease of Use

The Pragmatic LCD monitors deliver a superior picture with razor sharp images and brilliant colors. Designed for Digital Signage / Retail advertising applications use, this set comes complete with low-voltage DC input and directional speaker interface to the built-in audio amplifier.

#### Designed for Digital Signage applications

- No electrical outlets needed near the monitor
- Display can be up to 100 ft. away from AC outlet
- Only low voltage Cat5e/Cat6 wiring needed
- Certified electricians not need for installation
- Simple connection to PHA directional speaker
- Full HD 1920 x 1080p resolution
- Available with optional integral media player
- Power ON/OFF control via network / program
- · Built-in HDMI audio decoding in the monitor
- Optional sizes from 22" to 55" available

#### Best total cost of ownership

- Five Star Service-One-year advanced exchange warranty. With the option to extend up to 3 years
- Energy saver design

#### Sustainable and Safe

- · Eco-friendly Design
- · Flame retardant housing

#### Supports common media player interface

\* DVI-D, HDMI, VGA, etc.



Commercial

www.Pragmatic1.com Government

2340A Walsh Avenue, Santa Clara, CA 95051 Ph: 408-748-1100. Fax: 408-663-9783 Email: sales@pragmatic1.com

Copyright © 1994- 2014. All rights reserved.

#### **Integrated low voltage DC Interface**

An easy to use low voltage DC interface eliminates need for certified electricians or high-voltage outlets.

#### **High Definition Display**

Full HD for high resolution playback of media content with vibrant colors and images.

#### **UL Compliant**

Complies with all applicable UL certifications

#### **Wall Mountable**

Standard VESA 200mm x 200mm wall mount

DC input on low voltage interface



Low voltage DC power hub PPH-1

Directional speaker interface connector



US and International Patents pending. Copyright 1994-2014 Specifications and Design Subject to Change Without Notice

# Pragmatic PDS42

# **Digital Signage Monitor**

# 4277 Pragmatic Digital Signage Monitor

# Front View 38.9"

# Top View

Width = 38.9" Height = 24.7" Depth = 3.9"

VESA wall mounts available

### **Specifications**

Viewable Image Size	42"
Brightness (typical)	450 cd/m2
Contrast Ratio	5000:1
Response Time	6.5ms Gray-Gray
Resolution (typical)	Widescreen 1920x1080, 16:9 Aspect Ratio
Maximum Resolution	1920×1080x60Hz
Colors Supported	16.7 Million
Viewing Angle	Horizontal: 176°/Vertical: 176°
DVI-D input	1
HDMI Input	1
Analog RGB (D-sub15)	1
ENERGY STAR ® Compliant	Yes
Regulation: cULus	Yes
Regulation: FCC	Yes
Regulation: ROHS	Yes



2340A Walsh Avenue, Santa Clara, CA 95051 Ph: 408-748-1100, Fax: 408-663-9783 Email: sales@pragmatic1.com

Copyright © 1994- 2014. All rights reserved.

